



| "A" rozmiar | A | B | MXL | Siła docisku | "A" Size | A | B | MXL | Siła docisku |
|----------------|----|-----|-------|-----------------|-------------|----|-----|---------|-----------------|
| φ17-19 | 18 | 0.6 | M5X40 | 5NM | φ92-97 | 24 | 0.8 | M8X70 | 23NM |
| φ20-22 | 18 | 0.6 | M5X40 | | φ98-103 | 24 | 0.8 | M8X75 | |
| φ23-25 | 18 | 0.6 | M5X40 | | φ104-112 | 24 | 0.8 | M8X75 | |
| φ26-28 | 18 | 0.6 | M5X40 | | φ113-121 | 24 | 0.8 | M8X75 | |
| φ29-31 | 20 | 0.6 | M6X50 | 13NM | φ122-130 | 24 | 0.8 | M8X75 | 35NM |
| φ32-35 | 20 | 0.6 | M6X50 | | φ131-139 | 26 | 1.0 | M10X85 | |
| φ36-39 | 20 | 0.6 | M6X50 | | φ140-148 | 26 | 1.0 | M10X85 | |
| φ40-43 | 20 | 0.6 | M6X50 | 13NM | φ149-161 | 26 | 1.0 | M10X85 | |
| φ44-47 | 22 | 0.8 | M6X55 | | φ162-174 | 26 | 1.0 | M10X85 | |
| φ48-51 | 22 | 0.8 | M6X55 | | φ175-187 | 26 | 1.0 | M10X100 | |
| φ52-55 | 22 | 0.8 | M6X55 | | φ188-200 | 26 | 1.0 | M10X100 | |
| φ56-59 | 22 | 0.8 | M6X55 | | φ201-213 | 26 | 1.0 | M10X100 | |
| φ60-63 | 22 | 0.8 | M6X55 | 23NM | φ214-226 | 26 | 1.0 | M10X100 | |
| φ64-67 | 22 | 0.8 | M6X55 | | φ227-239 | 26 | 1.0 | M10X100 | |
| φ68-73 | 24 | 0.8 | M8X70 | | φ240-252 | 26 | 1.0 | M10X100 | |
| φ74-79 | 24 | 0.8 | M8X70 | | | | | | |
| φ80-85 | 24 | 0.8 | M8X70 | | | | | | |
| φ86-91 | 24 | 0.8 | M8X70 | | | | | | |

Nota:

1. B, T N stal galwanizowana, pozostałe części stal nierdzewna
2. Gładka krawędź